


Submitted Model No.: \_\_\_\_\_

Specific Features: \_\_\_\_\_



**RP78575▲ 1.75 GPM Touch-Clean® Shower Head**

Full Spray   
 Full Spray w/ Massage   
 Pause

Fast Massage  
 Soft Drenching Spray

4 15/16" (125 mm)  
 3 7/16" (87 mm)

**RP51303▲ (Pull-Up Diverter)**

5 1/2" (140 mm)  
 2 3/4" (70 mm)

**RP53237▲ (Non-Diverter)**

5 1/2" (140 mm)  
 2 3/4" (69 mm)

**RP70173▲ 1.75 GPM H<sub>2</sub>O Shower Head**

Full Spray

3" (76 mm)  
 6 13/32" (162 mm)

**RP77992 Available Extension Kit**

▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

DSP-B-T17038 Rev. H



see what Delta can do™

# TUB AND SHOWER FAUCET TRIM

- Lahara® Bath Collection
- Valve Only (T17038 Series)
- Shower Only (T17238 Series)
- Tub/Shower (T17438 Series)

## FEATURES:

- Monitor® 17 Series pressure balanced bath mixing valve trim
- "H<sub>2</sub>O" models include H<sub>2</sub>Okinetic® Technology shower head

## STANDARD SPECIFICATIONS:

- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system
- For use with MultiChoice® Universal rough valve body (R10000 Series)
- Back-to-back installation capability
- Solid brass forged body
- Lever volume control handle; temperature adjustment dial
- Field adjustable to limit handle rotation into hot water zone
- Maximum dial rotation adjustable between 90° and 180°
- All parts replaceable from the front of the valve
- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Tub port maximum flow rate 6.2 gpm @ 60 psi with R10000-UNBX
- Shower arm overall horizontal length = 5 1/2" (138 mm), including threaded ends
- Stem extension kit RP77992 can be ordered to allow for an additional 1 3/4" wall thickness. RP77992 ships with chrome escutcheon screws. For special finishes also order RP12630 escutcheon screws in desired finish.

## WARRANTY

- Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) - 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



## COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASSE 1016
- Indicates compliance to ICC/ANSI A117.1 - Valve control only
- EPA WaterSense® - Applies to T17238, T17238-H<sub>2</sub>O, T17438, T17438-H<sub>2</sub>O, RP78575 and RP70173 only

## Delta Faucet Company

55 E 111th Street, Indianapolis, Indiana 46280  
 350 South Edgeware Road, St. Thomas, ON N5P 4L1  
 © 2020 Delta Faucet Company