



GUTTER | ROOF

SILICONE ULTRA
100% Silicone Sealant



White Lightning® Silicone Ultra is a premium 100% silicone, high performance sealant that features superior adhesion to many surfaces. It provides a weathertight seal that remains flexible and is tough enough to stand up to the elements. White Lightning® Silicone Ultra is water ready in three hours. Ideal for sealing gutters, flashing, downspouts, lap joints, roof vents and siding. For use on: aluminum/metal, concrete, mortar, plastic, rubber, stone, vinyl & wood.

- Superior Adhesion to Metal, Wood, Masonry & Vinyl
- Weatherproof and Watertight Seal
- Permanently Flexible
- Non-Shrinking



WATER PROOF



EXTERIOR

PART #	UPC	Color	SIZE
W43101010	0-23275-00117-6	Clear	10 fl oz





SPECIALTY Silicone Ultra

Product Description:

White Lightning® Silicone Ultra is a premium 100% silicone, high performance sealant that features superior adhesion to many surfaces. It provides a weathertight seal that remains flexible and is tough enough to stand up to the elements. White Lightning® Silicone Ultra is water ready in three hours. Ideal for sealing gutters, flashing, downspouts, lap joints, roof vents and siding. For use on: aluminum/metal, concrete, mortar, plastic, rubber, stone, vinyl & wood.

Physical Properties:

Type: 100% Silicone

Colors: Clear

Shelf Life: 12 Months

Flash Point: >200°F

Flammability: N/A

Full Cure Time: 24 Hours

Tack Free Time: 30 Minutes at 75°F

Application Temperature: -20°F to 122°F

Service Temperature: -60°F to 300°F

Vehicle: Solvent Based

Solids by Weight: 96.9%

Weight/Gallon: 8.69 lbs/gal

Paintable: Not paintable

Primers: Not required

Mildew Resistance: Excellent

Water resistance: Excellent

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: N/A

Shelf Life: 12 Months

Clean Up: Mineral spirits, promptly clean tools and excess caulk; wash hands with soap and water.

Flexibility: Excellent

Linear Coverage: 9oz cartridge 21 ft at 1/4" wide x 1/4" deep bead.

Paintable: Not paintable

ASTM: Exceeds ASTM C-920, Class 25. Meets or exceeds performance requirements of Federal Specification TT-S-001543A Class A (COM-NBS) for silicone building sealants and TT-S-00230C Class A (COM-NBS) for one-component sealants.

Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

9oz cartridge

- Unscrew nozzle, cut cartridge nub, and screw on nozzle.
- Cut tip at 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Mineral spirits, promptly clean tools and excess caulk; wash hands with soap and water.

Cautions:

See SDS

LIMITED WARRANTY:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com